

# **LED Streetlights**

"Changing our Glow for Efficiency"

The City of Los Angeles Experience








# **City of Los Angeles Facts**



- **√** 2<sup>nd</sup> largest City in the USA
- √472 sq mi
- √6500 miles of streets
- **✓** Population of 4 Million
- **√** \$7.2 Bi. City Budget for 2012
- **✓** Power Utility owned by the City





# **Bureau of Street Lighting**



One of five Bureaus in the Department of Public Works, Est. in 1925



215,000 streetlights with over 400 different styles



4500 miles of streets are illuminated



# **Bureau of Street Lighting Operations**



Street Lighting
 Maintenance Assessment
 Fund



 All maintenance and engineering work In-House 214 Employees



\$25 Mil. Annual Budget –
 Appropriation for FY 12/13










- Converted 140,000 streetlights to LED
- Installed Remote Monitoring System
- Timeline 4 years
- Total Cost \$57 million
- Loan \$40 million
- City crews
- Program payback 7 years
- Launched February 2009





# Program Geographic Area




LED Conversion of 140,000 streetlights in the City of Los Angeles




# City of LA LED Program








# City of LA LED Program










# **Testing and Evaluation**





**Evaluation/Test** 

<u>Lighting Evaluation</u> Illumination, Luminance, Uniformity Ratio, Color Temperature, Brightness.

Electrical Evaluation Power consumption, Power Factor, Harmonic Distortion, Remote Monitoring Device compatibility, Remote Dimming/Controls.

#### **Mechanical Evaluation**

Disconnects, fixture assembly and ease of installation.



# **Summary of City of LA Specifications**



- 4000 K
- Warranty 10 years
- 70% delivery of initial lumens at 60,000 hours
- Minimum of 60% energy savings
- 3-prong twist-lock PE receptacle
- House-side light control
- Size, Weight, Packaging, Initial Lumens, and Efficacy
- Bureau's Webpage: http://bsl.lacity.org







- Improved Lighting
- No Cost
- No Negative Impact
- Surveys
- Dedicated telephone line
- Website http://bsl.lacity.org






# **LED Conversion Project**



## **Implementation Process**





## **Statistics**

 Jobs Created Manufacturer: 227 City of LA: 15

Truck rentals: 7 No. of Crews: 7








# Workload

Weekly Installations: 1,000



# City of Los Angeles LED Conversion Project






Local and Major Streets





# City of Los Angeles – Bureau of Street Lighting LED Conversion Project







# **Yearly Comparisons**



#### **Local Street LED Fixture**

#### 2009

•Avg. Price = \$ 432

•Efficacy = 42 Lm/W

•Life = 80,000 hrs

•Warranty = 5 yrs

#### 2010

•Avg. Price = \$ 298

•Efficacy = 61 Lm/W

•Life = 111,000 hrs

•Warranty = 6 yrs

#### 2011

•Avg. Price = \$ 285

•Efficacy = 72 Lm/W

•Life >150,000 hrs

•Warranty = 6 yrs

#### 2012

•Avg. Price = \$ 245 Efficacy = 81 Lm/W

•Life >150,000 hrs Warranty = 7 yrs



# **Yearly Comparisons**



**Local Street LED Fixture** 


### 2013

Avg. Price = \$ 141
 Efficacy = 96 Lm/W
 Life > 150,000 hrs
 Warranty = 10 yrs














# Completion of LED Street Lighting Energy Efficiency Program Phase I















Before 200 W HPS(240 W)

6th Street Bridge over Los Angeles River







**AFTER** 180 W LED (180 W)

6th Street Bridge over Los Angeles River



# 6<sup>th</sup> Street Bridge over LA River
















La Brea Avenue (HPS)







La Brea Avenue (LED)







Ventura Blvd. (HPS)









Ventura Blvd. (LED)





100W HPS (138 W)



70W LED (70W)







Ocean Front Walk, Venice – (HPS)







Ocean Front Walk, Venice – (LED)







•Single Streetlight Repairs


FY 2009: 23,500

FY 2013: 13,000

•Total Streetlight Repairs

FY 2010: 70,000

FY 2013: 43,800





# **LED Advantage**



- ➤ Reduced Energy Use, Increased Energy Savings
- ➤ White Light, Improved Color Rendering & Visibility
- ➤ Directional Light Source, Dimmable, Improved Uniformity
- ➤ Longer Life, Reduced Maintenance
- > Reduced light pollution, Dark Skies
- > House Side Shields
- > Smaller size, light weight
- ➤ Minimal end of life landfill waste, no mercury
- > Reduced wire/conduit size, for new construction
- > Instant on. No warm up period

#### Failure Comparison (average)


HID – **10**% (based on past installation history)

LED - **0.3**% (based on 400 units from 140,000 installed)



# Dirt and Lumen Depreciation (Lighting Level Analysis)







## **LED Program Results**



**2013** 

**ENERGY USAGE** 

**ENERGY COST** 

**ENERGY SAVINGS** 

TOTAL STREETLIGHT **REPAIRS** 

**PERFORMANCE** 

**COMMUNITY FEEDBACK** 

**INSTALLATIONS** 

**REMOVED HID UNITS** 

190 million kW/year \$16 million/year

40%

70,000

**Uniformity a Concern** 

**Anticipated Negative** 20 / day

Recycle old units

110 million kW/year \$8.8 million/year

63%

46,300

Good Uniformity, better than HPS

**Mostly Positive** 

30 / day

**Auction and Recycle** \$1,161,097 in revenue

ROADLIGHTING 2014 Auckland, New Zealand





# Crime Statistics (Incidents between hours of 7 PM to 7 AM)

CRIME TYPES	YEAR		REDUCTION
	2009	2013	
Theft from Vehicle	15,778	13,772	12.71 %
Burglary-Robbery-Theft	19,967	18,182	8.94 %
Vandalism	11,115	9,321	16.14 %
Total	46,860	41,275	11.9 %




#### **LED Program**

# BUREAU OF STREET LIGHTING DEPARTMENT OF PURLS WORKS

#### **Crime Reduction**

#### (Incidents between hours of 7 PM to 7 AM)






#### **Cost Breakdown**



(Local Street LED Fixture)



Unit Cost Breakdown for 2013/14 Fiscal Year - LED Program

TOTAL
COST PER
UNIT = \$188








- •2080 foot-long divided tunnel under LAX
- •Built in 1953 as part of State Highway 1
- •Old Lighting System High Pressure Sodium
- •New Lighting System 572 LED fixtures, Range: 30-120 LED's
- •Energy Savings: 64%
- Wireless Remote Controls System



### Sepulveda Tunnel under LAX





**400W HPS Light pipe** 



### Sepulveda Tunnel under LAX







572 LED fixtures, 64% energy savings 300 cd/m<sup>2</sup>



## Sepulveda Tunnel under LAX









### **3rd STREET TUNNEL**





42 fixtures (HPS & MV) 16,230 watts







114 LED (Teardrop & Tunnel) 14,084 watts







	# of Units		Lighting Levels		Energy Consumption		Energy
	Before	After	Before	After	Before	After	Savings
Sepulveda Tunnel	750	572	300 cd/m <sup>2</sup>	300 cd/m <sup>2</sup>	378kW	107kW	64%
3rd Street Tunnel	42	114	2 cd/m²	30 cd/m <sup>2</sup>	16.2kW	14kW	13.2%

#### **New Streetlight Applications**



Smart Meters





Solar to Grid

**EV Charging Stations** 



Telecommunications Equipment



**Remote Monitoring** 




**Security Cameras** 



### **Remote Monitoring System**

BUREAU OF STREET LIGHTING CONTRIBUTE OF PAIRS.

- 215,000 streetlights in the City of Los Angeles
- 54,027 street lighting controls installed
- Majority installed over the first
   3 years (with our LED program)





## **Remote Monitoring System**



- System utilizes mesh network and gateway
- Server hosted by manufacturer
- Provide streetlight diagnostics (operations, power consumption etc.)
- On/Off ability
- Lighting Control integrated in PE cell
- No GPS self activation. Manually activated with a Bar Code scanner





### **Remote Monitoring System**

BUREAU OF STREET LIGHTING DEPARTMENT OF PUBLIC WORKS

- Deployment Challenges
  - Stickers and bar coding
  - Cumbersome Process
  - Too much inputting
  - Too many devices
  - Too much time for activation
  - Field crew vs. contractor
- Interference 3G, 4G to what's next.
- Ornamental Systems







# Remote Monitoring System Street Lighting Control - Future Needs



- Better commissioning deployment
  - GPS built-in option
  - Remote activation
- Meter grade accuracy (2% or less)
- Flexibility for use with decorative systems
- Power back-up system on devices
- No monitoring fees
- Cost Reduction more affordable
- Systems Compatibility Standardization
- No Cabinets







# "Moving Forward" LED Decorative Fixtures



48 LEDs; 54 W



4100 K

48 LEDs; 80 W



3000 K

32 LEDs; 48 W



2900 K

42 LEDs; 55 W



2800 K

- More than 50,000 existing decorative fixtures
- About 400 different styles
- Color Temperature range 3000 Kelvin
- Presently testing and evaluating LED and Induction units



Typical post-top fixture



# "Moving Forward" LED Decorative Fixtures









ROADLIGHTING 2014 Auckland, New Zealand









800 – 1780 lumens, 2700 K



### "Moving Forward"

#### **Evaluation Test Site for New Lighting Technologies**










# Los Angeles Basin – View from Mt. Wilson Before LED Retrofit Project – 2008








# Los Angeles Basin – View from Mt. Wilson After LED Retrofit Project – 2012











#### **THANK YOU**

City of Los Angeles

**Bureau of Street** Lighting

http://bsl.lacity.org